



# Power over Ethernet

HI-NET TECHNOLOGY CO., LTD.

PRODUCTS  
SELECTING TYPE MANUAL

### S1005-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100Mbps PoE
- 1x10/100Mbps RJ45
- 1G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1008-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100Mbps PoE
- 4x10/100Mbps RJ45
- 1G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1008-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 1G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1005E-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100Mbps PoE
- 1x10/100Mbps RJ45
- 1G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- One Key CCTV Mode
- Desktop

### S1005F-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100Mbps PoE
- 1x100Mbps SFP
- 1G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- One Key CCTV Mode
- Desktop

### S1005SC-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100Mbps PoE
- 1x100Mbps SC Fiber
- 1G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- One Key CCTV Mode
- Desktop

### S1009E-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 1x10/100Mbps RJ45
- 1.8G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- One Key CCTV Mode
- Desktop

### S1009F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 1x100Mbps SFP
- 1.8G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- One Key CCTV Mode
- Desktop

### S1009SC-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 1x100Mbps SC Fiber
- 1.8G Switching capacity
- 1K MAC address
- AC Adapter 65 or 96 or 135W
- One Key CCTV Mode
- Desktop

### S1010E-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 2x10/100/1000Mbps RJ45
- 5.6G Switching capacity
- 8K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1010F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 2x1000Mbps SFP
- 5.6G Switching capacity
- 8K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1010EF-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 2x10/100/1000Mbps RJ45/SFP
- 5.6G Switching capacity
- 8K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1605-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100/1000Mbps PoE
- 1x10/100/1000Mbps RJ45
- 10G Switching capacity
- 2K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1608-4P



- IEEE802.3af & IEEE802.3at
- 4x10/100/1000Mbps PoE
- 4x10/100/1000Mbps RJ45
- 16G Switching capacity
- 8K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1608-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 16G Switching capacity
- 8K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1609E-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 1x10/100/1000Mbps RJ45
- 18G Switching capacity
- 4K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1609F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 1x1000Mbps SFP
- 18G Switching capacity
- 4K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1609SC-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 1x1000Mbps SC Fiber
- 18G Switching capacity
- 4K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S1610F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 2x10/100/1000Mbps SFP
- 20G Switching capacity
- 8K MAC address
- AC Adapter 65 or 96 or 135W
- Unmanaged
- Desktop

### S2009E-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 1x10/100Mbps RJ45
- 1.8G Switching capacity
- 1K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- Desktop

### S2009F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 1x10/100Mbps SFP
- 1.8G Switching capacity
- 1K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2010E-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 2x10/100/1000Mbps RJ45
- 5.6G Switching capacity
- 8K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2010F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 2x1000Mbps SFP
- 5.6G Switching capacity
- 8K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2010EF-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100Mbps PoE
- 2x10/100/1000Mbps RJ45/SFP
- 5.6G Switching capacity
- 8K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2609E-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 1x10/100/1000Mbps RJ45
- 18G Switching capacity
- 4K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2609F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 1x1000Mbps SFP
- 18G Switching capacity
- 4K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2610F-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 20G Switching capacity
- 8K MAC address
- Build-in AC-DC 150 or 270W
- Unmanaged
- 13" 1U Rack-mount

### S2016-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100Mbps PoE
- 3.2G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- Unmanaged
- 19" 1U Rack-mount

### S2024-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100Mbps PoE
- 8x10/100Mbps RJ45
- 4.8G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- Unmanaged
- 19" 1U Rack-mount

### S2024-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100Mbps PoE
- 4.8G Switching capacity
- 8K MAC address
- Build-in AC-DC 400 or 500W
- Unmanaged
- 19" 1U Rack-mount

### S2018-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100Mbps PoE
- 2x10/100/1000Mbps Combo
- 7.2G Switching capacity
- 4K MAC address
- Build-in AC-DC 270 or 500W
- Unmanaged
- 19" 1U Rack-mount

### S2026-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100Mbps PoE
- 2x10/100/1000Mbps Combo
- 8.8G Switching capacity
- 4K MAC address
- Build-in AC-DC 400 or 500W
- Unmanaged
- 19" 1U Rack-mount

### S2618R-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 36G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- Web-Smart Managed
- 19" 1U Rack-mount

### S2626R-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 52G Switching capacity
- 8K MAC address
- Build-in AC-DC 400 or 500W
- Web-Smart Managed
- 19" 1U Rack-mount

### S2218-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100Mbps PoE
- 2x10/100/1000Mbps Combo
- 7.2G Switching capacity
- 4K MAC address
- Build-in AC-DC 270 or 500W
- Web-Smart Managed
- 19" 1U Rack-mount

### S2226-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100Mbps PoE
- 2x10/100/1000Mbps Combo
- 8.8G Switching capacity
- 4K MAC address
- Build-in AC-DC 400 or 500W
- Web-Smart Managed
- 19" 1U Rack-mount

### S2818-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 36G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- Web-Smart Managed
- 19" 1U Rack-mount

### S2826-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 52G Switching capacity
- 8K MAC address
- Build-in AC-DC 400 or 500W
- Web-Smart Managed
- 19" 1U Rack-mount

### S2318-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100Mbps PoE
- 2x10/100/1000Mbps Combo
- 7.2G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- L2+ Full Managed
- 19" 1U Rack-mount

### S2326-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100Mbps PoE
- 2x10/100/1000Mbps Combo
- 8.8G Switching capacity
- 8K MAC address
- Build-in AC-DC 400 or 500W
- L2+ Full Managed
- 19" 1U Rack-mount

### S2912-8P



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps PoE
- 4x1000Mbps SFP
- 24G Switching capacity
- 8K MAC address
- Build-in AC-DC 150 or 270W
- L2+ Full Managed
- 13" 1U Rack-mount

### S2918R-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 36G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- L2+ Full Managed
- 19" 1U Rack-mount

### S2926R-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps PoE
- 2x1000Mbps SFP
- 52G Switching capacity
- 8K MAC address
- Build-in AC-DC 400 or 500W
- L2+ Full Managed
- 19" 1U Rack-mount

### S2918-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps PoE
- 2x1000Mbps SFP (combo)
- 32G Switching capacity
- 8K MAC address
- Build-in AC-DC 270 or 500W
- L2+ Full Managed
- 19" 1U Rack-mount

### S2928-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps PoE
- 4x1000Mbps SFP (combo)
- 48G Switching capacity
- 8K MAC address
- Build-in AC-DC 400 or 500W
- L2+ Full Managed
- 19" 1U Rack-mount

### S3020-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps PoE
- 4x1000Mbps SFP
- 40G Switching capacity
- 16K MAC address
- Build-in AC-DC 270 or 500W
- L3 Lite Managed
- 19" 1U Rack-mount

### S3028-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps PoE
- 4x1000Mbps SFP
- 56G Switching capacity
- 16K MAC address
- Build-in AC-DC 400 or 500W
- L3 Lite Managed
- 19" 1U Rack-mount

### S5020-16P



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps PoE
- 4x10Gbps SFP
- 112G Switching capacity
- 16K MAC address
- Build-in AC-DC 270 or 500W
- L3 Lite Managed
- 19" 1U Rack-mount

### S5028-24P



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps PoE
- 4x10Gbps SFP
- 128G Switching capacity
- 16K MAC address
- Build-in AC-DC 400 or 500W
- L3 Lite Managed
- 19" 1U Rack-mount

### PE15



- IEEE802.3af
- 1x10/100/1000Mbps Channel
- 15.4W Power on 2-pairs
- 52VDC Output Voltage
- Build-in AC-DC Power Supply
- UL/cUL, ICES, GS, SAA, CCC, KC, PSE, NOM, S-mark, BSMI, EAC, BIS, FCC, CE, ROHS

### PE30



- IEEE802.3at
- 1x10/100/1000Mbps Channel
- 30W Power on 2-pairs
- 52VDC Output Voltage
- Build-in AC-DC Power Supply
- UL/cUL, ICES, GS, SAA, CCC, KC, PSE, NOM, S-mark, BSMI, EAC, BIS, FCC, CE, ROHS

### PE60



- IEEE802.3at-4pairs
- 1x10/100/1000Mbps Channel
- 60W Power on 4-pairs
- 52VDC Output Voltage
- Build-in AC-DC Power Supply
- UL/cUL, ICES, GS, SAA, CCC, KC, PSE, NOM, S-mark, BSMI, EAC, BIS, FCC, CE, ROHS

### PE908



- IEEE802.3af & IEEE802.3at
- 8x10/100/1000Mbps Channel
- Up to 30W Power on 2-pairs
- 52VDC Output Voltage
- Build-in AC-DC 150 or 270W
- 12" 1U Rack-mount
- CE, FCC, C-Tick

### PE912



- IEEE802.3af & IEEE802.3at
- 12x10/100/1000Mbps Channel
- Up to 30W Power on 2-pairs
- 52VDC Output Voltage
- Build-in AC-DC 200 or 400W
- CE, FCC, C-Tick
- 19" 1U Rack-mount

### PE916



- IEEE802.3af & IEEE802.3at
- 16x10/100/1000Mbps Channel
- Up to 30W Power on 2-pairs
- 52VDC Output Voltage
- Build-in AC-DC 270 or 500W
- CE, FCC, C-Tick
- 19" 1U Rack-mount

### PE924



- IEEE802.3af & IEEE802.3at
- 24x10/100/1000Mbps Channel
- Up to 30W Power on 2-pairs
- 52VDC Output Voltage
- Build-in AC-DC 400 or 720W
- CE, FCC, C-Tick
- 19" 1U Rack-mount

### PX101



- IEEE802.3af & IEEE802.3at
- 1x10/100Mbps Channel
- Up to 22W Power on 2-pairs
- Extend PoE and LAN 100meter
- No additional power supply
- Easy plug-and-play installation
- Compact size, Wall-Mountable

### PX201



- IEEE802.3af & IEEE802.3at
- 1x10/100/1000Mbps Channel
- Up to 22W Power on 2-pairs
- Extend PoE and LAN 100meter
- No additional power supply
- Easy plug-and-play installation
- Compact size, Wall-Mountable

### PS13G



- IEEE802.3af
- 1x10/100/1000Mbps Channel
- Splits the 48VDC and LAN
- Convert 48VDC to 5/9/12V
- Wide input 36VDC to 57VDC
- Fixed output 5V or 9V or 12V
- Up to 12W DC output
- High efficiency DC/DC

### PS12G



- IEEE802.3af
- 1x10/100/1000Mbps Channel
- Splits the 48VDC and LAN
- Convert 48VDC to 5/9/12V
- Wide input 36VDC to 57VDC
- Adjustable output 5V, 9V, 12V
- Up to 12W DC output
- High efficiency DC/DC

### PS20G



- IEEE802.3af & IEEE802.3at
- 1x10/100/1000Mbps Channel
- Splits the 48VDC and LAN
- Convert 48VDC to 5/9/12V
- Wide input 36VDC to 57VDC
- Adjustable output 5V, 9V, 12V
- Up to 24W DC output
- High efficiency DC/DC

### Contact us

#### Shenzhen Hi-Net Technology Co., Ltd

3F, 4 Building, Anda Industrial Zone, Chongqing Rd, Fuyong Town, Baoan District, Shenzhen City, Guangdong Province, PR China

TEL: 86-755-23706700

FAX: +86-755-27330546

E-mail: sales@szhi-net.com

Web-side: www.szhi-net.com

